

SSI/MSDS/LAR/1 Issue No. : 2; Rev. No. 1 Date : 10.12,2018

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name ARGON, REFRIGERATED LIQUID

SDS no SSI/MSDS/LAR/1

Chemical description ARGON, REFRIGERATED LIQUID

CAS No : 7440-37-1 EC no : 231-147-0 EC index no : ---

Registration-No. Listed in Annex IV / V REACH, exempted from registration.

Chemical formula Ar

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use, Test gas/Calibration gas,

Purge gas, diluting gas, inerting gas, Purging, Laboratory use, Use for manufacture of electronic/photovoltaic components, Shield gas for welding processes, Contact supplier for more

information on uses, Medical applications

Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification : SICGILSOL India Pvt Ltd

Plot S-2, Phase III, Sipcot industrial complex, Nellikuppam, Walajapet Taluk, Ranipet-632405

Mob.No: 09677237866 http://www.sicgilsol.com/

1.4. Emergency telephone number

Emergency telephone number : Mob.No : 09677237866

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards : Gases under pressure : Compressed gas H280

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) : Warning

Hazard statements (CLP) : H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Precautionary statements (CLP)

- Prevention: P282 - Wear cold insulating gloves, face shield, eye protection

- Response: P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice / attention

- Storage : P403 - Store in a well-ventilated place

SECTION 3: Composition/information on ingredients

3.1. Substance

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ARGON, REFRIGERATED	CAS No : 7440-37-1	100	Press. Gas (Ref. Liq.), H281
LIQUID	(EC no) 231-147-0		
	EC index no :		
	(Registration-No.) *1		

^{*1:} Listed in Annex IV / V REACH, exempted from registration.

Full text of H-statements see section 16.

(3.2. Mixture : Not applicable

^{*2:} Registration deadline not expired.

^{*3:} Registration not required: Substance manufactured or imported < 1t/y.



SSI/MSDS/LAR/1 Issue No.: 2: Rev. No. 1 Date: 10.12.2018

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

 Skin contact Adverse effects not expected from this product. - Eve contact Adverse effects not expected from this product.

Ingestion is not considered a potential route of exposure. - Inaestion

4.2. Most important symptoms and effects, both acute and delayed Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media Water spray or fog.

- Unsuitable extinguishing media Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products None.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heatradiation

> may cause gas receptacles to rupture. Cool endangered receptacles with water sprayjet from a protected position. Prevent water used in emergency cases from entering sewers anddrainage systems.If possible, stop flow of product.Use water spray or fog to knock down fire fumes if

possible. Move containers away from the fire area if this can be done without risk.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for Special protective equipment for fire fighters

firefighters.Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with fullface mask.Standard EN 469 - Protective clothing for firefighters. Standard - EN 659:

Protective gloves forfirefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release. Evacuate area. Monitor concentration of released product. Wear selfcontained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Act in accordance with local emergency plan.

Stay upwind.

None 6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product : The product must be handled in accordance with good industrial hygiene and safety procedures.

> Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not breathe gas. Avoid release of product

into atmosphere.

Refer to supplier's container handling instructions Do not allow backfeed into the Safe handling of the gas receptacle

> container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.Leave valve protection caps in place until the container has been secured against either a wallor bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or

modify container



SSI/MSDS/LAR/1 Issue No. : 2; Rev. No. 1 Date : 10.12.2018

valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylindercontents. Containers should be stored in the vertical position and properly secured to prevent them fromfalling over.

7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

7.3. Specific end use(s) : None

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL (Occupational Exposure Limits) : No data available. DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration): No data available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

- A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.
- Eye/face protection
 Wear safety glasses with side shields. Wear goggles and a face shield when transfilling or breaking transfer connections Standard EN 166 - Personal eye-protection - specifications

Skin protection

- Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk.

- Other : Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

Respiratory protection
 Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Thermal hazards
 Wear cold insulating gloves when transfilling or breaking transfer connections

Standard EN 511 - Cold insulating gloves

8.2.3. Environmental exposure controls : None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas.
Colour : Colourless.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH value : Not applicable.

ARGON
(LIQUID, REFRIGERATED)

SSI/MSDS/LAR/1 Issue No. : 2; Rev. No. 1 Date : 10.12.2018

Molar mass40 g/molMelting point-189 °CBoiling point-186 °C

Flash point : Not applicable for gases and gas mixtures.

Critical temperature [°C] -122 °C

Evaporation rate (ether=1) : Not applicable for gases and gas mixtures.

Flammability range : Non flammable.

Vapour pressure [20°C] : Not applicable.

Vapour pressure [50°C] : Not applicable.

Relative density, gas (air=1) 1.38
Relative density, liquid (water=1) 1.4
Solubility in water 67.3 mg/l

Partition coefficient n-octanol/water : Not applicable for inorganic gases.

Auto-ignition temperature : Not applicable.

Viscosity [20°C] : Not applicable.

Explosive Properties : Not applicable

Oxidising Properties : None

SECTION 10: Stability and reactivity

10.1. Reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability
: Stable under normal conditions.

10.3. Possibility of hazardous reactions : None.

10.4. Conditions to avoid : None under recommended storage and handling conditions (see section 7)

10.5. Incompatible materials For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products : None

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : No toxicological effects from this product. Skin corrosion/irritation Serious : No known effects from this product. eye damage/irritation : No known effects from this product. Respiratory or skin : No known effects from this product. sensitisation Germ cell : No known effects from this product. mutagenicity Carcinogenicity : No known effects from this product. Toxic for reproduction: Fertility : No known effects from this product. : No known effects from this product. Toxic for reproduction : unborn child STOT-single exposure : No known effects from this product. STOT-repeated exposure : No known effects from this product. **Aspiration hazard** : Not applicable for gases and gas mixtures.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product

EC50 48h - Daphnia magna [mg/l]

EC50 72h - Algae [mg/l]

LC50 96 h - Fish [mg/l]

No data available.

No data available.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Other adverse effects : Can cause frost damage to vegetation.

Effect on the ozone layer : None.
Effect on global warming : None.

------Page 4 of 6



SSI/MSDS/LAR/1 Issue No. : 2; Rev. No. 1 Date : 10.12.2018

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required, May be vented to atmosphere Do not discharge into any place where its accumulation could be dangerous Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org for more guidance on suitable disposal

methods

List of hazardous waste codes (from

: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

Commission Decision 2001/118/EC)

: None.

13.2. Additional information

SECTION 14: Transport information

14.1. UN number : 1951

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : ARGON, REFRIGERATED LIQUID
Transport by air (ICAO-TI / IATA-DGR) : ARGON, REFRIGERATED LIQUID
Transport by sea (IMDG) : ARGON, REFRIGERATED LIQUID

14.3. Transport hazard class(es)

Labelling : 2.2 : Non-flammable, non-toxic gases

NON-FLAMMABLE GAS 2

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 3A
Hazard identification number : 22

Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other

carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Su: : 2.2

Transport by sea (IMDG)

 Class / Div. (Su :
 : 2.2

 Schedule (EmS) - Fire Emergency
 : F-C

 Schedule (EmS) - Spillage
 : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P203

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 202
Cargo Aircraft only : 202
Transport by sea (IMDG) P203

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what

to do in the event of an accident or an emergency. Before transporting product containers:

Ensure there is adequate ventilation.Ensure that containers are firmly secured.

- Ensure cylinder valve is closed and not leaking.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.Ensure valve protection device (where provided) is correctly fitted.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.



SSI/MSDS/LAR/1
Issue No. : 2; Rev. No. 1

Date: 10.12.2018

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Seveso Directive: 2012/18/EU (Seveso III) : Not covered.

National regulations

National legislation : Ensure all national/local regulations are observed.

Water hazard cl:

Kenn-Nr. : 1348

15.2. Chemical safety assessment : A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.

Training advice : Receptacle under pressure.

Further information : This Safety Data Sheet has been established in accordance with the applicable European

Union legislation. Classification in accordance with the calculation methods of Regulation (EC)

Full text of H- and EUH-statements		
Press. Gas (Ref. Liq.)	Gases under pressure : Refrigerated liquefied gas	
H281	Contains refrigerated gas; may cause cryogenic burns or injury.	

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document

------Page 6 of 6