

# MATERIAL SAFETY DATA SHEET



**NITRIC OXIDE**

SSI/MSDS/NOG/1  
Issue No. : 2; Rev. No. 1  
Date : 10.12.2018

**Danger**



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name : Nitric oxide  
SDS no : SSI/MSDS/NOG/1  
Chemical description : Nitric oxide  
CAS-No. : 10102-43-9  
EC-No. : 233-271-0  
EC Index-No. : ---  
Registration-No. : Registration deadline not expired.  
Chemical formula : NO

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use. Test gas/Calibration gas.Laboratory use. Chemical reaction / Synthesis. Use for manufacture of electronic/photovoltaic components. Contact supplier for more information on uses  
Uses advised against : Consumer use.

### 1.3. Details of the supplier of the safety data sheet

Company identification : SICGILSOL India Pvt Ltd  
Plot S-2,Phase III,Sipcot industrial complex,  
Nellikuppam,Walajapet Taluk,Ranipet-632405  
Mob.No : 09677237866  
<http://www.sicgilsol.com/>

### 1.4. Emergency telephone number

Emergency telephone number : Mob.No : 09677237866

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Oxidising Gases, Category 1	H270
	Gases under pressure : Compressed gas	H280
Health hazards	Specific target organ toxicity — Single exposure, Category 3, Narcosis	H330
	Skin corrosion/irritation, Category 1B	H314
	Serious eye damage/eye irritation, Category 1	H318

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazard statements (CLP) : H270- May cause or intensify fire; oxidizer.  
H280- Contains gas under pressure; may explode if heated.  
H330- Fatal if inhaled.  
H314- Causes severe skin burns and eye damage.  
EUH071 - Corrosive to the respiratory tract.

Precautionary statements (CLP)

Prevention : P220- Keep away from combustible materials.  
P244- Keep valves and fittings free from oil and grease.  
P260- Do not breathe gas, vapours.  
P280- Wear protective gloves, protective clothing, eye protection, face protection.

Response : P303+P361+P353+P315 - IF ON SKIN : (or hair) Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Get immediate medical advice / attention.  
P304+P340+P315 - IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention.  
P305+P351+P338+P315 - IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice / attention.

Storage : P370+P376 - In case of fire: stop leak if safe to do so.  
P403 - Store in a well-ventilated place.

Storage : P405 - Store locked up.

### 2.3. Other hazards

: Asphyxiant in high concentrations. Contact with liquid may cause cold burns/frostbite

# MATERIAL SAFETY DATA SHEET



## NITRIC OXIDE

SSI/MSDS/NOG/1  
Issue No. : 2; Rev. No. 1  
Date : 10.12.2018

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances :

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
NITRIC OXIDE	(CAS-No.) 10102-43- 9 (EC-No.) 233-271-0 (EC Index-No.) --- (Registration-No.) *2	100	Ox. Gas 1, H270 Press. Gas (Comp.), H280 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1B, H314

# MATERIAL SAFETY DATA SHEET



## NITRIC OXIDE

SSI/MSDS/NOG/1  
Issue No. : 2; Rev. No. 1  
Date : 10.12.2018

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*2: Registration deadline not expired.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of H-statements see section 16.

**3.2. Mixtures** : Not applicable

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

### **4.2. Most important symptoms and effects, both acute and delayed**

- : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of coordination. Refer to section 11

### **4.3. Indication of any immediate medical attention and special treatment needed**

- : Treat with corticosteroid spray as soon as possible after inhalation. Obtain medical assistance

## **SECTION 5: Fire-fighting measures**

### **5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

### **5.2. Special hazards arising from the substance or mixture**

- Specific hazards : Supports combustion., Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None that are more hazardous than the product itself.

### **5.3. Advice for firefighters**

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water sprayjet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

- : Try to stop release. Evacuate area. Monitor concentration of released product. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Act in accordance with local emergency plan. Stay upwind.

### **6.2. Environmental precautions**

- : Try to stop release. Reduce vapour with fog or fine water spray. Monitor concentration of released product.

### **6.3. Methods and material for containment and cleaning up**

- : Hose down area with water. Ventilate area. Wash contaminated equipment or sites of leaks with copious quantities of water

### **6.4. Reference to other sections**

- : See also sections 8 and 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

- Safe use of the product : The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consult supplier for specific recommendations. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Avoid exposure, obtain special instructions before use. Use no oil or grease. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature.

# MATERIAL SAFETY DATA SHEET



## NITRIC OXIDE

SSI/MSDS/NOG/1

Issue No. : 2; Rev. No. 1

Date : 10.12.2018

Contact your gas supplier if in doubt. Installation of a cross purge assembly between the cylinder and the regulator is recommended. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into atmosphere.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and

contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Open valve slowly to avoid pressure shock.

### 7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

### 7.3. Specific end use(s)

: None

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Nitric oxide (10102-43-9)		
OEL : Occupational Exposure Limits		
EU	TWA IOELV (EU) 8 h [mg/m <sup>3</sup> ]	30 mg/m <sup>3</sup>
	TWA IOELV (EU) 8 h [ppm]	25 ppm

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration) : No data available.

### 8.2.1. Appropriate engineering controls

: Product to be handled in a closed system and under strictly controlled conditions. Provide adequate general and local exhaust ventilation. Preferably use permanent leak-tight installations (e.g. welded pipes). Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Gas detectors should be used when toxic gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

### 8.2.2. Individual protection measures, e.g. personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection

: Wear safety glasses with side shields. Wear goggles and a face shield when transfilling or breaking transfer connections. Standard EN 166 - Personal eye-protection - specifications

• Skin protection

- Hand protection

: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk. Wear chemically resistant protective gloves. Standard EN 374 - Protective gloves against chemicals. Consult glove manufacturer's product information on material suitability and material thickness. The breakthrough time of the selected gloves must be greater than the intended use period.

- Other

: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear. Keep suitable chemically resistant protective clothing readily available for emergency use. Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals

# MATERIAL SAFETY DATA SHEET



## NITRIC OXIDE

SSI/MSDS/NOG/1  
Issue No. : 2; Rev. No. 1  
Date : 10.12.2018

- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. Recommended: Filter NO (blue). Consult respiratory device supplier's product information for the selection of the appropriate device. Gas filters do not protect against oxygen deficiency. Standard EN 14387 - Gas filter(s), combined filter(s) and full face mask - EN 136. Keep self contained breathing apparatus readily available for emergency use. Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems. Standard EN
  - Thermal hazards : None
- 8.2.3. Environmental exposure controls** : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.



### **SECTION 9: Physical and chemical properties**

#### **9.1. Information on basic physical and chemical properties**

Physical state at 20°C / 101.3kPa	: Gas.
Colour	: Brownish gas.
Odour	: Poor warning properties at low concentrations.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
pH value	Not applicable.
Molar mass	30 g/mol
Melting point	-164 °C
Boiling point	-152 °C
Flash point	: Not applicable for gases and gas mixtures.
Critical temperature [°C]	-93 °C
Evaporation rate (ether=1)	: Not applicable for gases and gas mixtures.
Flammability range	: Non flammable.
Vapour pressure [20°C]	Not applicable.
Vapour pressure [50°C]	Not applicable.
Relative density, gas (air=1)	1
Relative density, liquid (water=1)	1.3
Solubility in water	67 mg/l
Partition coefficient n-octanol/water	: Not applicable for inorganic gases.
Auto-ignition temperature	: Not applicable.
Viscosity [20°C]	: Not applicable.
Explosive Properties	: Not applicable.
Oxidising Properties	: Oxidiser.
- Coefficient of oxygen equivalency (Ci)	0.3

#### **9.2. Other information**

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below.

#### **10.2. Chemical stability**

: Stable under normal conditions. Decomposes at room temperature to other nitrogen oxides and nitrogen. Oxidises in air to form nitrogen dioxide which is extremely reactive

#### **10.3. Possibility of hazardous reactions**

Violently oxidises organic material, May react violently with reducing agents

#### **10.4. Conditions to avoid**

Heat

#### **10.5. Incompatible materials**

May react violently with reducing agents. May react violently with combustible materials. Air. For additional information on compatibility refer to ISO 11114.

#### **10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced

### **SECTION 11: Toxicological information**

#### **11.1. Information on toxicological effects**

Acute toxicity	: Delayed fatal pulmonary oedema possible.LC50 inhalation rat (ppm) 57.5 ppm/4h
Skin corrosion/irritation	: Severe corrosion to skin at high concentrations.
Serious eye damage/irritation	: Severe corrosion to the eyes at high concentrations.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: Severe corrosion to the respiratory tract at high concentrations.
STOT-repeated exposure	: Severe corrosion to the respiratory tract at high concentrations.
Aspiration hazard	: Not applicable for gases and gas mixtures.

# MATERIAL SAFETY DATA SHEET



**NITRIC OXIDE**

SSI/MSDS/NOG/1

Issue No. : 2; Rev. No. 1

Date : 10.12.2018

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Assessment : No data available.  
EC50 48h - Daphnia magna [mg/l] No data available.  
EC50 72h - Algae [mg/l] No data available.  
LC50 96 h - Fish [mg/l] No data available.

### **12.2. Persistence and degradability**

Assessment : Not applicable for inorganic gases.

### **12.3. Bioaccumulative potential**

Assessment : No data available.

### **12.4. Mobility in soil**

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.

### **12.5. Results of PBT and vPvB assessment**

Assessment : No data available.

### **12.6. Other adverse effects**

: May cause pH changes in aqueous ecological systems.  
Effect on the ozone layer : None.  
Effect on global warming : No known effects from this product.  
Effect on global warming : When discharged in large quantities may contribute to the greenhouse effect  
Contains greenhouse gas(es)

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

Contact supplier if guidance is required. May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.

List of hazardous waste codes (from Commission Decision 2001/118/EC)

: 16 05 04 : Gases in pressure containers other than those mentioned in 16 05 04.

### **13.2. Additional information**

: None.

## **SECTION 14: Transport information**

### **14.1. UN number**

: 1660

### **14.2. UN proper shipping name**

**Transport by road/rail (ADR/RID)** : NITRIC OXIDE, COMPRESSED

**Transport by air (ICAO-TI / IATA-DGR)** : NITRIC OXIDE, COMPRESSED

**Transport by sea (IMDG)** : NITRIC OXIDE, COMPRESSED

### **14.3. Transport hazard class(es)**

**Labelling** :



2.3 : Toxic gases  
5.1 : Oxidizing substances  
8 : Corrosive substances

### **Transport by road/rail (ADR/RID)**

Class : 2  
Classification code : 1 TOC  
Hazard identification number : 225  
Tunnel Restriction : D - Passage forbidden through tunnels of category D and E

### **Transport by air (ICAO-TI / IATA-DGR)**

Class / Div. (Su) : 2.3 (5.1, 8)

### **Transport by sea (IMDG)**

Class / Div. (Su) : 2.3 (5.1, 8)  
Schedule (EmS) - Fire Emergency : : F-C  
Schedule (EmS) - Spillage : : S-W

### **14.4. Packing group**

Transport by road/rail (ADR/RID) : Not applicable  
Transport by air (ICAO-TI / IATA-DGR) : Not applicable  
Transport by sea (IMDG) : Not applicable

### **14.5. Environmental hazards**

Transport by road/rail (ADR/RID) : None.  
Transport by air (ICAO-TI / IATA-DGR) : None.  
Transport by sea (IMDG) : None.

# MATERIAL SAFETY DATA SHEET



## NITRIC OXIDE

SSI/MSDS/NOG/1  
Issue No. : 2; Rev. No. 1  
Date : 10.12.2018

### 14.6. Special precautions for user

#### Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200  
Transport by air (ICAO-TI / IATA-DGR)  
Passenger and Cargo Aircraft : Forbidden  
Cargo Aircraft only : Forbidden  
Transport by sea (IMDG) : P200  
Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:  
- Ensure there is adequate ventilation.  
- Ensure that containers are firmly secured.  
- Ensure cylinder valve is closed and not leaking.  
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
- Ensure valve protection device (where provided) is correctly fitted.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

Restrictions on use : None  
Seveso Directive : 2012/18/EU (Seveso III) Covered.

#### National regulations

National legislation : Ensure all national/local regulations are observed.  
Water hazard cl : -  
Kenn- Nr 285

### 15.2. Chemical safety assessment

: CSA has not yet been carried out.

## SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.  
Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training. Receptacle under pressure.  
Further information : This Safety Data Sheet has been established in accordance with the applicable European Union legislation. Classification in accordance with the calculation methods of Regulation (EC) 1272/2008 CLP.

### Full text of H- and EUH-statements

Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H330	Fatal if inhaled
EUH071	Corrosive to the respiratory tract

### DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**